

NSN 3040-00-517-5196 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-517-5196 **Thread Class:** 2a both ends **Thread Direction:** Right-hand both ends Thread Length: 1.000 inches both ends **Overall Length:** 24.031 inches **Wrenching Facility Outside Diameter:** 0.750 inches and 1.000 inches both ends Tip Length: 0.156 inches and 0.875 inches both ends **Shank Outside Diameter:** 0.500 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Unef both ends **Core Diameter:** 0.150 inches **Thread Location:** Internal first end **End Type:** Square male second end Width Across Flats: 1.000 inches both ends **End Connection Type:** Threaded external both ends

Setscrew:

Not included both ends

**Casing Material:** 

Steel

**Wrenching Facility Type:** 

Knurled surface both ends

**Cross Section Size And Location:** 

0.187 inches diameter first end

**Casing Surface Treatment:** 

Zinc coated

**Casing Length Between Ferrules:** 

24.000 inches

**Casing Outside Diameter:** 

0.445 inches

## **NSN 3040-00-517-5196**Flexible Shaft Assembly - Page 2 of 2



Swivel End:
Not provided both ends
Enddiameter:
0.875 inches and 1.000 inches both ends
_ubrication Fitting:
Not provided both ends
Corelength:
25.031 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
5.000 inches
Special Features:
Rd permanent keyed drive end
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
Г246-е