NSN 3040-00-517-5198

Wrenching Facility Outside Diameter:

Thread Class: 2a both ends

Thread Direction:
Right-hand both ends
Overall Length:
74.641 inches

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-517-5198

0.000	3 inches both ends
Thre	ad Depth:
0.313	3 inches both ends
Tip L	ength:
0.640) inches and 0.828 inches both ends
Shan	nk Outside Diameter:
0.531	1 inches both ends
Core	Material:
Steel	
Scre	w Thread Series Designator:
Uns b	both ends
Core	Diameter:
0.150) inches
Thre	ad Location:
Interr	nal both ends
End	Туре:
Squa	are female first end
End	Connection Type:
Threa	aded internal both ends
Sets	crew:
Not in	ncluded both ends
Casi	ng Material:
Steel	
Wren	nching Facility Type:
Knurl	led surface both ends
Cros	s Section Size And Location:
0.185	5 inches across flats first end
Casi	ng Surface Treatment:
Zinc	coated
Casi	ng Length Between Ferrules:
72.50	00 inches
Casi	ng Outside Diameter:
0.438	3 inches
Swiv	rel End:
Not p	provided both ends

NSN 3040-00-517-5198

Flexible Shaft Assembly - Page 2 of 2



Enddiameter:
1.000 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
73.391 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
6.000 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e