

NSN 3040-00-517-5200 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-517-5200 **Thread Class:** 2a both ends **Thread Direction:** Right-hand both ends Thread Length: 0.250 inches both ends **Overall Length:** 9.406 inches **Wrenching Facility Outside Diameter:** 0.938 inches both ends Tip Length: 0.422 inches and 1.000 inches both ends **Shank Outside Diameter:** 0.500 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.150 inches **Thread Location:** Internal both ends **End Type:** Square male second end **End Connection Type:** Threaded internal both ends Setscrew: Not included both ends **Casing Material:** Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.187 inches diameter first end

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

8.000 inches

Casing Outside Diameter:

0.445 inches

Swivel End:

Not provided both ends

NSN 3040-00-517-5200Flexible Shaft Assembly - Page 2 of 2



Enddiameter:
1.000 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
9.406 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
6.000 inches
Special Features:
Rd permanent keyed drive end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T046 o