

NSN 3040-00-517-5205 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-517-5205 **Thread Class:** 2a both ends **Thread Direction:** Right-hand both ends **Overall Length:** 241.141 inches Thread Depth: 0.313 inches both ends Tip Length: 0.640 inches and 0.828 inches both ends **Shank Outside Diameter:** 0.531 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.150 inches **Thread Location:** Internal both ends **End Type:** Square female both ends Width Across Flats: 0.938 inches both ends **End Connection Type:** Union ferrule both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

240.000 inches

Casing Outside Diameter:

0.438 inches

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

NSN 3040-00-517-5205Flexible Shaft Assembly - Page 2 of 2



Lubrication Fitting:
Not provided both ends
Corelength:
241.891 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
6.000 inches
Special Features:
0.185 in. Sq first endgo.187 in. Nom diameter second end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e