NSN 3040-00-517-5223



	Flexible Shaft Assembly - Page 1 of 2	Gr
	View Online at https://aerobasegroup.com/nsn/3040-00-517-5223	
,	Thread Direction:	
	Right-hand both ends	
	Overall Length:	
	313.109 inches	
	Wrenching Facility Outside Diameter:	
	0.953 inches both ends	
	Thread Depth:	
	0.375 inches both ends	
	Tip Length:	
,	0.640 inches and 0.828 inches first end	
	Shank Outside Diameter:	
,	0.534 inches both ends	
	Core Material:	
	Steel	
	Screw Thread Series Designator:	
	Uns both ends	
	Core Diameter:	
,	0.150 inches	
,	Thread Location:	
	Internal both ends	
	End Type:	
	Square female second end	
	End Connection Type:	
	Threaded internal both ends	
	Setscrew:	
	Not included both ends	
	Casing Material:	
	Steel	
	Wrenching Facility Type:	
	Knurled surface both ends	
	Cross Section Size And Location:	
	0.185 inches across flats second end	
	Casing Surface Treatment:	
	Galvanized	

Casing Length Between Ferrules:

312.000 inches

Casing Outside Diameter:

0.438 inches

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

NSN 3040-00-517-5223

Flexible Shaft Assembly - Page 2 of 2



Lubrication Fitting:		
Not provided both ends		
Corelength:		
312.984 inches		
Core Rotation Direction:		
Clockwise or counterclockwise		
Core Removability:		
Removable		
Minimum Operating Radius:		
6.000 inches		
Special Features:		
Permanent keyed drive end		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		

Fiig: T246-e