NSN 3040-00-517-5229

Flexible Shaft Assembly - Page 1 of 2



Tromble enant toodinary Trage 1 of 2	aroup
View Online at https://aerobasegroup.com/nsn/3040-00-517-5229	
Thread Class:	
2a both ends	
Thread Direction:	
Right-hand both ends	
Overall Length:	
103.625 inches	
Thread Depth:	
0.500 inches both ends	
Tip Length:	
0.500 inches and 1.125 inches both ends	
Shank Outside Diameter:	
0.594 inches both ends	
Core Material:	
Steel	
Screw Thread Series Designator:	
Uns both ends	
Core Diameter:	
0.185 inches	
Thread Location:	
Internal both ends	
End Type:	
Round keyed both ends	
Width Across Flats:	
0.938 inches both ends	
End Connection Type:	
Union ferrule both ends	
Setscrew:	
Not included both ends	
Casing Material:	
Steel	
Wrenching Facility Type:	
Hexagon both ends	
Cross Section Size And Location:	
0.187 inches diameter both ends	
Casing Surface Treatment:	
Zinc coated	

Casing Outside Diameter:

Casing Length Between Ferrules:

0.438 inches

102.000 inches

Swivel End:

Not provided both ends

NSN 3040-00-517-5229Flexible Shaft Assembly - Page 2 of 2



Enddiameter:
1.094 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
103.625 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Minimum Operating Radius:
6.000 inches
Special Features:
Rd permanent keyed end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T246-e