

View Online at <https://aerobasegroup.com/nsn/3040-00-517-5234>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Overall Length:

41.625 inches

Thread Depth:

0.500 inches both ends

Tip Length:

0.500 inches and 1.125 inches both ends

Shank Outside Diameter:

0.594 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.185 inches

Thread Location:

Internal both ends

End Type:

Round keyed both ends

Width Across Flats:

0.938 inches both ends

End Connection Type:

Threaded female or union ferrule both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.187 inches diameter both ends

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

40.000 inches

Casing Outside Diameter:

0.438 inches

Swivel End:

Not provided both ends

Enddiameter:

1.094 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

41.625 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Special Features:

Rd permanent keyed end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e