

View Online at <https://aerobasegroup.com/nsn/3040-00-517-5239>

**Thread Class:**

2a both ends

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.375 inches both ends

**Overall Length:**

18.625 inches

**Wrenching Facility Outside Diameter:**

0.953 inches both ends

**Tip Length:**

0.172 inches and 0.734 inches both ends

**Shank Outside Diameter:**

0.534 inches both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Uns both ends

**Core Diameter:**

0.150 inches

**Thread Location:**

Internal both ends

**End Type:**

Round keyed both ends

**End Connection Type:**

Union ferrule both ends

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Knurled surface both ends

**Cross Section Size And Location:**

0.152 inches diameter both ends

**Casing Surface Treatment:**

Galvanized

**Casing Outside Diameter:**

0.438 inches

**Casing Protective Device Type:**

Coiled spring protector

**Swivel End:**

Not provided both ends

**Enddiameter:**

1.000 inches both ends

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

18.406 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Minimum Operating Radius:**

6.000 inches

**Special Features:**

Permanent keyed @driveend, 8 in. Lg coiled spring protector at rd keyed drive end of shaft assembly

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T246-e