

View Online at <https://aerobasegroup.com/nsn/3040-00-517-5239>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Thread Length:

0.375 inches both ends

Overall Length:

18.625 inches

Wrenching Facility Outside Diameter:

0.953 inches both ends

Tip Length:

0.172 inches and 0.734 inches both ends

Shank Outside Diameter:

0.534 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Round keyed both ends

End Connection Type:

Union ferrule both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.152 inches diameter both ends

Casing Surface Treatment:

Galvanized

Casing Outside Diameter:

0.438 inches

Casing Protective Device Type:

Coiled spring protector

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

18.406 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Special Features:

Permanent keyed @driveend, 8 in. Lg coiled spring protector at rd keyed drive end of shaft assembly

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e