NSN 3040-00-517-5241

Flexible Shaft Assembly - Page 1 of 2



Flexible Shart Assembly - Fage 1 of 2	
View Online at https://aerobasegroup.com/nsn/3040-00-	517-5241
Thread Direction:	
Right-hand both ends	
Overall Length:	
229.094 inches	
Wrenching Facility Outside Diameter:	
0.954 inches both ends	
Thread Depth:	
0.313 inches both ends	
Tip Length:	
0.172 inches and 0.734 inches both ends	
Shank Outside Diameter:	
0.541 inches and 0.545 inches both ends	
Core Material:	
Steel	
Screw Thread Series Designator:	
Uns both ends	
Core Diameter:	
0.150 inches	
Thread Location:	
Internal both ends	
End Type:	
Round keyed both ends	
End Connection Type:	
Union ferrule both ends	
Setscrew:	
Not included both ends	
Casing Material:	
Steel	
Wrenching Facility Type:	
Knurled surface both ends	
Cross Section Size And Location:	
0.184 inches diameter both ends	
Casing Surface Treatment:	
Galvanized	
Casing Length Between Ferrules:	

228.000 inches

Casing Outside Diameter:

0.438 inches

Swivel End:

Not provided both ends

Enddiameter:

1.000 inches both ends

NSN 3040-00-517-5241

Flexible Shaft Assembly - Page 2 of 2



Lubrication Fitting:	
Not provided both ends	
Corelength:	
228.906 inches	
Core Rotation Direction:	
Clockwise	
Core Removability:	
Removable	
Minimum Operating Radius:	
6.000 inches	
Special Features:	
Permanent keyed drive end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

T246-e