

View Online at <https://aerobasegroup.com/nsn/3040-00-517-7756>

**End Similarity:**

Not identical

**Thread Length:**

0.313 inches second end, sixth portion

**Overall Length:**

4.110 inches

**Screw Thread Series Designator:**

Unc second end, sixth portion

**Shaft Thread Direction:**

Right-hand second end, sixth portion

**Teeth Hardness Rating:**

Between 30.0 rockwell c and 35.0 rockwell c

**Worm Thread Quantity:**

1

**Worm Thread Lead:**

0.1666 inches

**Worm Thread Direction:**

Left-hand

**Worm Pressure Angle In Deg:**

29.000

**Worm Helix Angle:**

5 degrees 52 min

**Worm Outside Diameter:**

0.622 inches

**Worm Pitch Diameter:**

0.518 inches

**Shaft Hardness Rating:**

Between 30.0 rockwell c and 35.0 rockwell c

**Worm Thread Section Length:**

0.944 inches

**Worm Body Length:**

1.000 inches

**Worm Body Tapered Bearing Surface End:**

Not provided

**Shaft Location:**

Both ends of worm

**Straight Unthreaded Length:**

0.853 inches second end, fifth portion

**Straight Unthreaded Section Diameter:**

0.625 inches second end, second portion

**Unthreaded Section Pin Hole Diameter:**

0.1090 inches second end, fifth portion

**Material:**

Steel

**Material:**

Steel

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated

**Fsc Application Data:**

Telescope, elbow, antiaircraft fire control equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T246-c