

View Online at <https://aerobasegroup.com/nsn/3040-00-528-0648>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Thread Length:

0.438 inches both ends

Spline Major Diameter:

0.271 inches both ends

Overall Length:

8.487 inches

Spline Quantity:

12 both ends

Spline Minor Diameter:

0.229 inches both ends

Tip Length:

0.500 inches both ends

Shank Outside Diameter:

0.445 inches both ends

Pitch Diameter:

0.250 inches both ends

Shoulder Outside Diameter:

0.563 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.250 inches

Thread Location:

Internal both ends

End Type:

Round, internal splined both ends

Width Across Flats:

0.750 inches both ends

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

14.5 both ends

Spline Length:

0.266 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.250 inches diameter both ends

Torsional Deflection Rating:

2 to 3-1/2 degrees in.-lb

Casing Length Between Ferrules:

8.000 inches

Casing Outside Diameter:

0.445 inches

Swivel End:

Provided both ends

Enddiameter:

0.563 inches both ends

Corelength:

8.000 inches

Core Rotation Direction:

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

10.000 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e