

View Online at <https://aerobasegroup.com/nsn/3040-00-528-1713>

Thread Class:

3a both ends

Thread Direction:

Right-hand both ends

Thread Length:

0.312 inches both ends

Spline Major Diameter:

0.258 inches both ends

Overall Length:

94.500 inches

Flange Thickness:

0.062 inches both ends

Spline Quantity:

12 both ends

Spline Minor Diameter:

0.156 inches both ends

Tip Length:

0.500 inches both ends

Shank Outside Diameter:

0.406 inches both ends

Pitch Diameter:

0.250 inches both ends

Shoulder Outside Diameter:

0.562 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Round, internal splined both ends

Width Across Flats:

0.750 inches both ends

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

14.5 both ends

Spline Length:

0.250 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.250 inches diameter both ends

Torsional Deflection Rating:

6 degrees ft-lb in.

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

93.500 inches

Casing Outside Diameter:

0.258 inches

Swivel End:

Not provided both ends

Enddiameter:

0.875 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

94.500 inches

Core Rotation Direction:

Clockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

3.500 inches

Fsc Application Data:

Miscellaneous aircraft accessories and components

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e