

View Online at <https://aerobasegroup.com/nsn/3040-00-540-8246>

Outside Diameter:

Between 0.339 inches and 0.349 inches

Internal Straight Key Width:

Between 0.015 inches and 0.020 inches

Thickness:

Between 0.132 inches and 0.138 inches

Bore Diameter:

Between 0.1560 inches and 0.1580 inches

Key Quantity:

1

Distance From Center Of Bore To Top Of Key:

0.103 inches

End Application:

Helicopter, advance attack ah-1w; helicopter, search & rescue hh-60h; helicopter, uscg search & rescue hh-60j; helicopter, carrier based asw, sh-60f; aircraft, hawkeye e-2c, f4s, tomcat f-14, c-2a (reprocured), viking s-3b

Securing Hole Quantity:

2

Angle Between Centerlines Of Securing Holes In Deg:

90.0

Screw Thread Series Designator And Location:

Single hole unf

Securing Hole Type And Location:

Threaded single hole

Criticality Code Justification:

Feat

Thread Size And Location:

0.750 inches single hole

Special Features:

Weapon system essential

Material:

Steel, qq-s-764, type 303, cond b-canceled

Material:

Steel comp 303

Material Specification:

Qq-s-764, type 303, cond b-canceled federal specification single material response

Style Designator:

Plain round

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A231a0