

View Online at <https://aerobasegroup.com/nsn/3040-00-554-6810>

Thread Class:

2a both ends

Thread Direction:

Right-hand both ends

Spline Major Diameter:

0.406 inches both ends

Overall Length:

81.000 inches

Spline Quantity:

12 both ends

Spline Minor Diameter:

0.250 inches both ends

Wrenching Facility Outside Diameter:

0.750 inches both ends

Thread Depth:

0.500 inches both ends

Tip Length:

0.625 inches both ends

Pitch Diameter:

0.250 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Uns both ends

Core Diameter:

0.150 inches

Thread Location:

Internal both ends

End Type:

Round, internal splined both ends

End Connection Type:

Threaded internal both ends

Spline Pressure Angle In Deg:

14.5 both ends

Spline Length:

0.250 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.406 inches diameter both ends

Torsional Deflection Rating:

6 degrees ft-lb in winding, 6 degrees ft-lb in unwinding

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

78.813 inches

Casing Outside Diameter:

0.265 inches

Casing Protective Device Type:

Rubber cover

Swivel End:

Not provided both ends

Enddiameter:

0.750 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

80.000 inches

Core Rotation Direction:

Counterclockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

3.500 inches

Special Features:

Core will rotate clockwise also

Specification Or Standard:

2 class

Fsc Application Data:

Radio set, radio navigational equipment, airborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e