

NSN 3040-00-554-6810 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-554-6810 **Thread Class:** 2a both ends **Thread Direction:** Right-hand both ends **Spline Major Diameter:** 0.406 inches both ends **Overall Length:** 81.000 inches **Spline Quantity:** 12 both ends **Spline Minor Diameter:** 0.250 inches both ends **Wrenching Facility Outside Diameter:** 0.750 inches both ends **Thread Depth:** 0.500 inches both ends Tip Length: 0.625 inches both ends Pitch Diameter: 0.250 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Uns both ends **Core Diameter:** 0.150 inches **Thread Location:** Internal both ends **End Type:** Round, internal splined both ends **End Connection Type:** Threaded internal both ends Spline Pressure Angle In Deg: 14.5 both ends Spline Length:

0.250 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

**Casing Material:** 

Steel

## NSN 3040-00-554-6810

Flexible Shaft Assembly - Page 2 of 2



| Wrenching Facility Type:                                 |
|--|
| Knurled surface both ends                                |
| Cross Section Size And Location:                         |
| 0.406 inches diameter both ends                          |
| Torsional Deflection Rating:                             |
| 6 degrees ft-lb in winding, 6 degrees ft-lb in unwinding |
| Casing Surface Treatment:                                |
| Galvanized   |
| Casing Length Between Ferrules:                          |
| 78.813 inches  |
| Casing Outside Diameter:                                 |
| 0.265 inches   |
| Casing Protective Device Type:                           |
| Rubber cover   |
| Swivel End:  |
| Not provided both ends                                   |
| Enddiameter:   |
| 0.750 inches both ends                                   |
| Lubrication Fitting:                                     |
| Not provided both ends                                   |
| Corelength:  |
| 80.000 inches  |
| Core Rotation Direction:                                 |
| Counterclockwise   |
| Core Removability:                                       |
| Nonremovable   |
| Minimum Operating Radius:                                |
| 3.500 inches   |
| Special Features:  |
| Core will rotate clockwise also                          |
| Specification Or Standard:                               |
| 2 class  |
| Fsc Application Data:                                    |
| Radio set, radio navigational equipment, airborne        |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| T246-e   |