NSN 3040-00-554-8026

Worm Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-554-8026

| End Similarity: | | | | |
|---|--|--|--|--|
| Not identical | | | | |
| Overall Length: | | | | |
| 8.875 inches | | | | |
| Worm Thread Quantity: | | | | |
| 10 | | | | |
| Worm Thread Lead: | | | | |
| 6.4815 inches | | | | |
| Worm Thread Direction: | | | | |
| Right-hand | | | | |
| Worm Pressure Angle In Deg: | | | | |
| 30.000 | | | | |
| Worm Helix Angle: | | | | |
| 37 degrees 34 min. | | | | |
| Worm Outside Diameter: | | | | |
| 3.008 inches | | | | |
| Worm Pitch Diameter: | | | | |
| 2.682 inches | | | | |
| Shaft Hardness Rating: | | | | |
| C scale, 34 max | | | | |
| Worm Thread Section Length: | | | | |
| 2.875 inches | | | | |
| Worm Body Length: | | | | |
| 4.500 inches | | | | |
| Worm Body Tapered Bearing Surface End: | | | | |
| Not provided | | | | |
| Shaft Location: | | | | |
| Both ends of worm | | | | |
| Straight Unthreaded Length: | | | | |
| 1.625 inches either end, first portion | | | | |
| Straight Unthreaded Section Diameter: | | | | |
| 1.000 inches either end, third portion | | | | |
| Unthreaded Section Keyway Width: | | | | |
| 0.1550 inches either end, third portion | | | | |
| Unthreaded Section Keyway Depth: | | | | |
| 0.172 inches either end, third portion | | | | |
| Special Features: | | | | |
| W/oil passage holes | | | | |
| Material: | | | | |
| Steel, mil-s-890, class hg | | | | |
| Material: | | | | |
| Steel, mil-s-890, class hg | | | | |

NSN 3040-00-554-8026

Worm Shaft - Page 2 of 2



| | | | | - |
|-----|----|-----|-----|-----|
| C I | 20 | lŧ. | l i | fe: |
| J. | 16 | | _, | ıc. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-c