NSN 3040-00-554-8035

Shouldered Shaft - Page 1 of 2

Externally and internally threaded

First End Style:

End Similarity:



View Online at https://aerobasegroup.com/nsn/3040-00-554-8035

| Not identical | |
|--|--|
| Second End Style: | |
| Circular groove, two cross drilled holes and externally threaded | |
| Second End Groove Width: | |
| 0.1250 inches | |
| Second End Groove Diameter: | |
| 1.0200 inches | |
| Overall Length: | |
| 58.375 inches | |
| First End Diameter: | |
| 1.6250 inches | |
| First End External Thread Length: | |
| 1.000 inches | |
| First End Internal Thread Length: | |
| 0.625 inches | |
| Second End Distance From End To Groove: | |
| 3.063 inches | |
| Second End Diameter: | |
| 1.2800 inches | |
| Second End Hole Diameter: | |
| 0.1880 inches | |
| Second End Distance From Hole Center To End: | |
| 0.188 inches | |
| Second End External Thread Length: | |
| 3.057 inches | |
| Second End Angle Between Holes: | |
| 90.0 degrees | |
| Step Quantity: | |
| 9 | |
| Largest Step Diameter: | |
| 1.625 inches | |
| Surface Finish: | |
| 125.0 microinches | |
| Material: | |
| Steel comp 4140 | |
| Material Specification: | |
| Mil-s-5626 military specification single material response | |
| Shelf Life: | |
| N/a | |
| | |

NSN 3040-00-554-8035

Shouldered Shaft - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A23200

Mil-std (military Standard):

Mil-s-5626 spec.