NSN 3040-00-560-8412

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-560-8412

| Eirot End Style |
|--|
| First End Style: |
| Splined (straight) |
| End Similarity: |
| Not identical |
| Second End Style: |
| Circular grooved, splined (straight) and externally threaded |
| Second End Groove Width: |
| 0.1090 inches |
| Second End Groove Diameter: |
| 2.2180 inches |
| Overall Length: |
| 15.09375 inches |
| First End Diameter: |
| Between 2.3420 inches and 2.3470 inches |
| First End Spline Length: |
| 3.250 inches |
| First End Spline Minor Diameter: |
| 2.0220 inches |
| First End Spline Major Diameter: |
| 2.3470 inches |
| Second End Distance From End To Groove: |
| 3.589 inches |
| Second End Diameter: |
| Between 2.3420 inches and 2.3470 inches |
| Second End Spline Length: |
| 3.7500 inches |
| Second End Spline Minor Diameter: |
| 2.0220 inches |
| Second End Spline Major Diameter: |
| 2.3470 inches |
| Second End Internal Thread Length: |
| 0.875 inches |
| Step Quantity: |
| 3 |
| First End Spline Quantity: |
| 10 |
| Second End Spline Quantity: |
| 10 |
| Largest Step Diameter: |
| 2.625 inches |
| Surface Finish: |
| 125.0 microinches |
| |

NSN 3040-00-560-8412

Shouldered Shaft - Page 2 of 2



Material:

Steel comp 8642 or steel comp 8645 or steel comp 4150

Material Specification:

Aisi assn standard all material responses

Fsc Application Data:

Differntial drive, tank full tracked

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A23200