# NSN 3040-00-563-5316

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-563-5316

# First End Style:

Cross drilled and externally threaded

### End Similarity:

Not identical

# Second End Style:

Two woodruff keyways and cross drilled hole

#### **Overall Length:**

5.000 inches

#### First End Diameter:

Between 0.5900 inches and 0.5903 inches

### First End Hole Diameter:

0.0730 inches

#### First End Distance From Hole Center To End:

0.078 inches

### First End External Thread Length:

0.250 inches

### Second End Keyway Width:

Between 0.1240 inches and 0.1260 inches

### Second End External Keyway Length:

0.953 inches

# Second End Keyway Depth:

0.062 inches

# Second End Distance From Keyway Center To End:

0.985 inches

#### Second End Diameter:

Between 0.5240 inches and 0.5245 inches

# Second End Distance From Hole Center To End:

0.438 inches

#### Second End Angle Between Keyways:

180.0 degrees

#### Step Quantity:

5

# Largest Step Diameter:

0.750 inches

# **Special Features:**

90 degrees angle between keyways and drilled holes; 2.094 in. Between groove centers

# Material:

Steel

# Fsc Application Data:

Engine electrical system components, non-aircraft

# Shelf Life:

N/a

# NSN 3040-00-563-5316

Shouldered Shaft - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A23200

