

View Online at <https://aerobasegroup.com/nsn/3040-00-585-1176>

Thread Class:

3a both ends

Thread Direction:

Right-hand both ends

Overall Length:

31.000 inches

Thread Depth:

0.469 inches both ends

Tip Length:

1.000 inches both ends

Shank Outside Diameter:

0.340 inches both ends

Tongue Thickness:

0.001 inches both ends

Core Material:

Steel

Screw Thread Series Designator:

Unef both ends

Core Diameter:

0.375 inches

Thread Location:

Internal both ends

End Type:

Square male both ends

Width Across Flats:

1.312 inches both ends

End Connection Type:

Threaded internal both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.302 inches diameter both ends

Torsional Deflection Rating:

0.5 degrees ft-lb in.

Casing Surface Treatment:

Zinc coated

Casing Length Between Ferrules:

29.000 inches

Casing Outside Diameter:

0.660 inches

Swivel End:

Not provided both ends

Enddiameter:

0.660 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

31.000 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Removable

Minimum Operating Radius:

6.000 inches

Fsc Application Data:

Aircraft gunnery fire control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e