NSN 3040-00-590-0234

Shouldered Shaft - Page 1 of 2

Steel comp 4150



View Online at https://aerobasegroup.com/nsn/3040-00-590-0234
First End Style:
Splined (involute)
End Similarity:
Not identical
Second End Style:
Externally threaded and flat keyway
Overall Length:
17.340 inches
First End Diameter:
Between 2.0060 inches and 2.0120 inches
First End Spline Length:
2.720 inches
First End Spline Minor Diameter:
Between 1.7340 inches and 1.7450 inches
First End Spline Major Diameter:
Between 2.0060 inches and 2.0120 inches
First End Pressure Angle:
40.0 degrees
First End Pitch Diameter:
1.8993 inches
Second End Keyway Width:
0.3200 inches
Second End External Keyway Length:
0.940 inches
Second End Keyway Depth:
0.190 inches
Second End Diameter:
1.5000 inches
Second End External Thread Length:
0.880 inches
Step Quantity:
6
First End Spline Quantity:
17
Largest Step Diameter:
Between 4.502 inches and 4.508 inches
Surface Finish:
16.0 microinches
Special Features:
3 notches in second end, 0.280 in. W, 0.190 in. Dp; 0.380 in. Lg; 6 mtg holes in largest diameter spline 3.625 bc, 7/16-14unc-2b threads,
holes 60 degrees apart
Material:

NSN 3040-00-590-0234

Shouldered Shaft - Page 2 of 2



Material Specification:
Mil-s-13048 military specification single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A23200

Mil-std (military Standard):

Mil-s-13048 spec.