NSN 3040-00-590-0234

Shouldered Shaft - Page 1 of 2

Steel comp 4150



| View Online at https://aerobasegroup.com/nsn/3040-00-590-0234 |
|---|
| First End Style: |
| Splined (involute) |
| End Similarity: |
| Not identical |
| Second End Style: |
| Externally threaded and flat keyway |
| Overall Length: |
| 17.340 inches |
| First End Diameter: |
| Between 2.0060 inches and 2.0120 inches |
| First End Spline Length: |
| 2.720 inches |
| First End Spline Minor Diameter: |
| Between 1.7340 inches and 1.7450 inches |
| First End Spline Major Diameter: |
| Between 2.0060 inches and 2.0120 inches |
| First End Pressure Angle: |
| 40.0 degrees |
| First End Pitch Diameter: |
| 1.8993 inches |
| Second End Keyway Width: |
| 0.3200 inches |
| Second End External Keyway Length: |
| 0.940 inches |
| Second End Keyway Depth: |
| 0.190 inches |
| Second End Diameter: |
| 1.5000 inches |
| Second End External Thread Length: |
| 0.880 inches |
| Step Quantity: |
| 6 |
| First End Spline Quantity: |
| 17 |
| Largest Step Diameter: |
| Between 4.502 inches and 4.508 inches |
| Surface Finish: |
| 16.0 microinches |
| Special Features: |
| 3 notches in second end, 0.280 in. W, 0.190 in. Dp; 0.380 in. Lg; 6 mtg holes in largest diameter spline 3.625 bc, 7/16-14unc-2b threads, |
| holes 60 degrees apart |
| Material: |

NSN 3040-00-590-0234

Shouldered Shaft - Page 2 of 2



| Material Specification: |
|---|
| Mil-s-13048 military specification single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A23200

Mil-std (military Standard):

Mil-s-13048 spec.