NSN 3040-00-592-9378

Friction Lining - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3040-00-592-9378

Fabrication Method:
Compressed and woven
Major Diameter:
18.000 inches
Thickness:
0.134 inches
Hole Arrangement Style:
Indefinite
Mounting Hole Diameter:
Between 0.404 inches and 0.406 inches
Minor Diameter:
8.000 inches
Friction Lining Material:
Asbestos composition
Lining Style:
Clutch disk
Application Type:
Dry
Hole Type And Quantity:
56 counterbored
Mounting Hole Circle Diameter:
5
16.750 inches and 13.250 inches and 9.250 inches
16.750 inches and 13.250 inches and 9.250 inches
16.750 inches and 13.250 inches and 9.250 inches Features Provided:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features: W/steel back plate
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features: W/steel back plate Shelf Life:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features: W/steel back plate Shelf Life: N/a
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features: W/steel back plate Shelf Life: N/a
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features: W/steel back plate Shelf Life: N/a Unit Of Measure:
16.750 inches and 13.250 inches and 9.250 inches Features Provided: Rigid friction lining Surface Condition And Location: Both sides ground Circular Pattern Hole Type And Quantity: 16 counterbored inner securing circle Attachment Method: Riveted Special Features: W/steel back plate Shelf Life: N/a Unit Of Measure: Demilitarization: