

View Online at <https://aerobasegroup.com/nsn/3040-00-618-2141>

Thread Class:

3b both ends

Thread Direction:

Right-hand both ends

Spline Major Diameter:

0.312 inches and 0.336 inches both ends

Overall Length:

44.125 inches

Spline Quantity:

14 both ends

Spline Minor Diameter:

0.243 inches and 0.271 inches both ends

Thread Depth:

0.266 inches and 0.328 inches both ends

Tip Length:

0.879 inches and 1.000 inches both ends

Pitch Diameter:

0.292 inches both ends

Core Material:

Steel, spring

Screw Thread Series Designator:

Unef both ends

Core Diameter:

0.375 inches

Thread Location:

Internal both ends

End Type:

Round, internal splined both ends

Width Across Flats:

0.875 inches and 1.000 inches both ends

End Connection Type:

Union ferrule both ends

Spline Pressure Angle In Deg:

30.0 both ends

Spline Length:

0.437 inches and 0.750 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Hexagon both ends

Cross Section Size And Location:

0.313 inches diameter both ends

Torsional Deflection Rating:

12 degrees ft lb in. Torsional deflection rating winding 16 degrees ft lb in. Torsional deflection rating unwinding

Casing Surface Treatment:

Rubber, chloroprene

Casing Length Between Ferrules:

42.433 inches

Casing Outside Diameter:

0.790 inches

Swivel End:

Not provided both ends

Enddiameter:

0.531 inches both ends

Lubrication Fitting:

Not provided both ends

Corelength:

44.215 inches

Core Rotation Direction:

Clockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

18.000 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T246-e