

View Online at https://aerobasegroup.com/nsn/3040-00-633-6653

NSN 3040-00-633-6653 Worm Shaft - Page 1 of 2 End Similarity: Not identical **Thread Length:** 0.188 inches second end, third portion **Overall Length:** 2.703 inches Screw Thread Series Designator: Unf second end, third portion **Shaft Thread Direction:** Right-hand second end, third portion **Distance From Radial Center To Flat Surface:** 0.0937 inches first end, fourth portion **Teeth Hardness Rating:** Between 35.0 rockwell c and 38.0 rockwell c Section Shape: D-shape first end, fourth portion Worm Thread Quantity: 2 Worm Thread Lead: 0.2618 inches Worm Thread Direction: **Right-hand** Worm Pressure Angle In Deg: 14.500 Worm Helix Angle: 9 degrees 28 min Worm Outside Diameter: 0.562 inches Worm Pitch Diameter: 0.500 inches Shaft Hardness Rating: Between 35.0 rockwell c and 38.0 rockwell c Worm Thread Section Length: 0.812 inches Worm Body Length: 1.2343 inches Worm Body Tapered Bearing Surface End: Not provided

Shaft Location:

Both ends of worm

Straight Unthreaded Length:

0.542 inches second end, first portion

NSN 3040-00-633-6653

Worm Shaft - Page 2 of 2



Straight Unthreaded Section Diameter:

0.2948 inches first end, third portion

Circular Portion Radius:

0.1249 inches first end, fourth portion

Material:

Steel, corrosion resisting

Material:

Stainless steel

Surface Treatment:

Passivate

Surface Treatment:

Passivated

Reference Number Differentiating Characteristics:

W/center drilled hole in end of shortest shaft Ig

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-c