NSN 3040-00-653-9606

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-653-9606	
Thread Class:	
2b both ends	
Thread Direction:	
Right-hand both ends	
Overall Length:	
22.875 inches	
Thread Depth:	
0.405 inches both ends	
Shank Outside Diameter:	
0.503 inches both ends	
Shoulder Outside Diameter:	
0.750 inches both ends	
Core Material:	
Steel	
Screw Thread Series Designator:	
Uns both ends	
Core Surface Treatment:	
Any acceptable	
Core Diameter:	
0.145 inches	
Thread Location:	
Internal both ends	
Width Across Flats:	
1.000 inches both ends	
Setscrew:	
Not included both ends	
Casing Material:	
Steel	
Wrenching Facility Type:	
Hexagon both ends	
Casing Surface Treatment:	
Any acceptable	
Casing Length Between Ferrules:	
17.500 inches	
Casing Outside Diameter:	
0.500 inches	
Cooling Protective Device Types	

Casing Protective Device Type:

Plastic cover

Swivel End:

Not provided both ends

Lubrication Fitting:

Not provided both ends

NSN 3040-00-653-9606

Flexible Shaft Assembly - Page 2 of 2



Corelength:
19.875 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T246-e