## NSN 3040-00-673-3170

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-673-3170

First E	End S	Style:
---------	-------	--------

Circular grooved and internally threaded

First End Groove Width:

0.1250 inches

First End Groove Diameter:

0.6250 inches

**End Similarity:** 

Not identical

**Second End Style:** 

Circular grooved and internally threaded

**Second End Groove Width:** 

0.5000 inches

**Second End Groove Diameter:** 

0.6250 inches

**Overall Length:** 

9.750 inches

First End Distance From End To Groove:

0.6190 inches

First End Diameter:

Between 0.7496 inches and 0.7501 inches

First End Internal Thread Length:

6.6250 inches

**Second End Distance From End To Groove:** 

0.5000 inches

**Second End Diameter:** 

Between 0.8500 inches and 0.8730 inches

Second End Internal Thread Length:

0.8750 inches

Step Quantity:

**Largest Step Diameter:** 

Between 1.1000 inches and 1.1250 inches

Surface Finish:

125.0 microinches

Material:

Steel comp 1040 or steel comp 1045

**Material Specification:** 

Qq-s-633 federal specification all material responses

**Fsc Application Data:** 

Fan drive, engine, nonaircraft

Shelf Life:

N/a

## NSN 3040-00-673-3170

Shouldered Shaft - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A23200