

View Online at <https://aerobasegroup.com/nsn/3040-00-673-7811>

Body Material:

Any acceptable

First End Outside Diameter:

0.625 inches

Mounting Provision:

Threaded mounting studs

Temperature Rating:

-15.0 degrees fahrenheit

Mounting Facility Length:

1.000 inches

Overall Height:

2.000 inches

Overall Width:

2.000 inches

Bore Diameter:

1.500 inches

Longest Horizontal Distance Between Mounting Centers:

1.428 inches

Longest Vertical Distance Between Mounting Centers:

1.428 inches

Mounting Facility Thread Direction:

Right-hand

First End External Thread Length:

1.000 inches

Compressed Length:

13.250 inches

Extended Length:

20.625 inches

Mounting Provision Arrangement Style:

Four stud square

Pressure Rating:

300.0 pounds per square inch

Features Provided:

Cushioned stroke

Mounting Facility Thread Series Designator:

Unf

Integral Valve Operation Method:

Pneumatic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Unf

First Piston Rod End Thread Diameter:

0.438 inches

First Piston Rod End Thready Qty Per Inch (tpi):

20

First Piston Rod End Thread Class:

2a

First Piston Rod End Thread Direction:

Right-hand

Piston Rod End Similarity:

Identical

Mounting Facility Pipe Thread Size:

0.250 inches

Port Location And Quantity:

2 cylinder head end

Port Thread Series Designator:

Npt

Port Thready Qty Per Inch (tpi):

18

Port Pipe Thread Size:

0.375 inches

Fsc Application Data:

Guide, launcher

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200