# NSN 3040-00-699-7993

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-699-7993

# First End Style:

Two circular grooves, splined and internally threaded

#### First End Groove Width:

Between 0.1300 inches and 0.1500 inches

#### First End Groove Diameter:

Between 2.8000 inches and 2.8200 inches

#### **End Similarity:**

Identical

# **Second End Groove Width:**

Between 0.1300 inches and 0.1500 inches

#### **Second End Groove Diameter:**

Between 2.8000 inches and 2.8200 inches

#### **Overall Length:**

22.100 inches

#### First End Distance From End To Groove:

0.134 inches

#### First End Diameter:

2.9600 inches

# First End Spline Minor Diameter:

2.8450 inches

# First End Spline Major Diameter:

Between 2.9800 inches and 2.9850 inches

#### First End Internal Thread Length:

1.500 inches

#### First End Distance Between First And Second Groove Centers:

Between 1.454 inches and 1.458 inches

# **Second End Distance From End To Groove:**

0.134 inches

# **Second End Diameter:**

2.9900 inches

# **Second End Spline Minor Diameter:**

2.8450 inches

# Second End Spline Major Diameter:

Between 3.0020 inches and 3.0025 inches

# Second End Internal Thread Length:

1.500 inches

#### Second End Distance Between First And Second Groove Centers:

Between 1.454 inches and 1.458 inches

# Step Quantity:

4

# First End Spline Quantity:

47

# **NSN 3040-00-699-7993** Shouldered Shaft - Page 2 of 2



Second End Spline Quantity:
47
Largest Step Diameter:
Between 3.1138 inches and 3.1250 inches
Material:
Steel comp 8640
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A23200