

View Online at <https://aerobasegroup.com/nsn/3040-00-701-2800>

**Outside Diameter:**

1.000 inches

**Thickness:**

0.380 inches

**Bore Diameter:**

Between 0.5000 inches and 0.5080 inches

**Securing Hole Quantity:**

2

**Angle Between Centerlines Of Securing Holes In Deg:**

180.0

**Securing Hole Type And Location:**

Unthreaded single hole

**Hole Diameter And Location:**

0.1280 inches all holes and 0.1330 inches all holes

**Surface Finish And Location:**

125 microinches inside periphery

**Material:**

Steel, qq-s-631, comp 1010-canceled or steel, qq-s-631, comp 1020-canceled or steel, qq-s-634, comp 1010-canceled or steel, qq-s-634, comp 1020-canceled or steel, qq-s-698

**Material:**

Steel comp 1010 or steel comp 1020 or steel comp 1010 or steel comp 1020 or steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020 or steel

**Material Specification:**

Qq-s-631, comp 1010-canceled federal specification 1st material response and qq-s-631, comp 1020-canceled federal specification 2nd material response and qq-s-634, comp 1010-canceled federal specification 3rd material response and qq-s-634, comp 1020-canceled federal specification 4th material response and qq-s-698 federal specification 5th material response

**Surface Treatment:**

Cadmium and chromate and zinc and chromate

**Style Designator:**

Plain round

**Surface Treatment:**

Cadmium, qq-p-416, type 2, class 2 and zinc, qq-z-325, type 2, class 3

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A231a0