

View Online at <https://aerobasegroup.com/nsn/3040-00-702-4011>

**Outside Diameter:**

0.470 inches

**Thickness:**

0.100 inches

**Bore Diameter:**

0.1880 inches

**Plain Hole Diameter:**

0.0700 inches

**Clamp Securing Hole Style:**

Threaded

**Screw Thread Series Designator:**

Unf

**Thread Size:**

0.060 inches

**Surface Finish And Location:**

125 microinches both bearing flats

**Material:**

Steel, qq-s-763

**Material:**

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Round, single bolt secured

**Surface Treatment:**

Passivated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A231a0