

View Online at <https://aerobasegroup.com/nsn/3040-00-702-8656>

Outside Diameter:

0.625 inches

Thickness:

0.312 inches

Bore Diameter:

Between 0.4370 inches and 0.4400 inches

Securing Hole Quantity:

2

Angle Between Centerlines Of Securing Holes In Deg:

180.0

Securing Hole Type And Location:

Unthreaded single hole

Criticality Code Justification:

Abxv

Hole Diameter And Location:

0.1285 inches single hole

Surface Finish And Location:

125 microinches inside periphery

Material:

Steel, qq-s-631, comp 1010-canceled or steel, qq-s-631, comp 1020-canceled or steel, qq-s-634, comp 1010-canceled or steel, qq-s-634, comp 1020-canceled

Material:

Steel comp 1010 or steel comp 1020 or steel comp 1010 or steel comp 1020

Material Specification:

Qq-s-631, comp 1010-canceled federal specification 1st material response and qq-s-631, comp 1020-canceled federal specification 2nd material response and qq-s-634, comp 1010-canceled federal specification 3rd material response and qq-s-634, comp 1020-canceled federal specification 4th material response

Surface Treatment:

Phosphate and phosphate zinc

Style Designator:

Plain round

Surface Treatment:

Phosphate, mil-p-16232, type m, class 3 and phosphate, mil-p-16232, type z, class 3 and anodized, f-20 3a, singer co, the simulation products div

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A231a0