

View Online at <https://aerobasegroup.com/nsn/3040-00-702-8656>

**Outside Diameter:**

0.625 inches

**Thickness:**

0.312 inches

**Bore Diameter:**

Between 0.4370 inches and 0.4400 inches

**Securing Hole Quantity:**

2

**Angle Between Centerlines Of Securing Holes In Deg:**

180.0

**Securing Hole Type And Location:**

Unthreaded single hole

**Criticality Code Justification:**

Abxv

**Hole Diameter And Location:**

0.1285 inches single hole

**Surface Finish And Location:**

125 microinches inside periphery

**Material:**

Steel, qq-s-631, comp 1010-canceled or steel, qq-s-631, comp 1020-canceled or steel, qq-s-634, comp 1010-canceled or steel, qq-s-634, comp 1020-canceled

**Material:**

Steel comp 1010 or steel comp 1020 or steel comp 1010 or steel comp 1020

**Material Specification:**

Qq-s-631, comp 1010-canceled federal specification 1st material response and qq-s-631, comp 1020-canceled federal specification 2nd material response and qq-s-634, comp 1010-canceled federal specification 3rd material response and qq-s-634, comp 1020-canceled federal specification 4th material response

**Surface Treatment:**

Phosphate and phosphate zinc

**Style Designator:**

Plain round

**Surface Treatment:**

Phosphate, mil-p-16232, type m, class 3 and phosphate, mil-p-16232, type z, class 3 and anodized, f-20 3a, singer co, the simulation products div

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A231a0