

View Online at <https://aerobasegroup.com/nsn/3040-00-704-1964>

Thread Class:

2a first end

Thread Direction:

Right-hand first end

Thread Length:

0.375 inches first end

Spline Major Diameter:

0.299 inches both ends

Overall Length:

49.000 inches

Spline Quantity:

12 both ends

Spline Minor Diameter:

0.243 inches both ends

Wrenching Facility Outside Diameter:

0.750 inches second end

Thread Depth:

0.375 inches first end

Tip Length:

1.000 inches both ends

End Application:

Test set, radio, jedts, type n0. An/arm-32

Shoulder Outside Diameter:

0.5625 inches first end

Core Material:

Steel

Screw Thread Series Designator:

Uns first end

Core Diameter:

0.150 inches

Thread Location:

Internal first end

End Type:

Round, external splined both ends

End Connection Type:

Threaded internal first end

Spline Pressure Angle In Deg:

14.0 both ends

Spline Length:

0.4375 inches both ends

Spline Type:

Involute both ends

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface second end

Cross Section Size And Location:

0.40625 inches diameter both ends

Torsional Deflection Rating:

18.0 in.-lb winding and 17.0 in.-lb unwinding torsional deflection

Casing Surface Treatment:

Galvanized

Casing Length Between Ferrules:

48.000 inches

Casing Outside Diameter:

0.295 inches

Casing Protective Device Type:

Plastic cover

Swivel End:

Provided second end

Enddiameter:

0.750 inches second end

Lubrication Fitting:

Not provided second end

Corelength:

48.000 inches

Core Rotation Direction:

Clockwise or counterclockwise

Core Removability:

Nonremovable

Minimum Operating Radius:

3.500 inches

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e