

View Online at <https://aerobasegroup.com/nsn/3040-00-731-5266>

**Shoulder Width:**

0.100 inches

**Shoulder Outside Diameter:**

3.312 inches

**Hub Inside Diameter:**

Between 0.752 inches and 0.753 inches

**First End Hub Outside Diameter:**

Between 1.052 inches and 1.072 inches

**Second End Hub Outside Diameter:**

Between 1.810 inches and 1.811 inches

**Distance From First End Hub To Shoulder:**

Between 0.770 inches and 0.780 inches

**Distance From Second End Hub To Shoulder:**

Between 0.365 inches and 0.385 inches

**Special Features:**

2nd end id 1.552 in.Min, 1.572 in.Max; one internal keyway at zero degrees on aa end 0.127 in.Nom w; 0.410 in.Max distance from bore center to key bottom; flange scalloped between bolt holes by 2.000 in.Radius; securing hole qty: 4; angle between centerlines of securing holes in deg: 90.0 degs; material hardness rating: 26.0 to 33.0 rockwell c; o/a length: 1.245 in.Nim, 1.250 in.Max; securing hole size: 0.266 in.Dia

**Material:**

Steel

**Material Specification:**

Comp 4130 federal specification single material response

**Surface Treatment:**

Chromate

**Style Designator:**

Double hub, split and solid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A523y0