## NSN 3040-00-735-9091

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-735-9091 First End Style: Plain **End Similarity:** Not identical Second End Style: Circular grooved, splined (straight) and externally threaded **Second End Groove Width:** Between 0.3200 inches and 0.3800 inches **Second End Groove Diameter:** 0.8600 inches **Overall Length:** 16.910 inches First End Diameter: Between 0.9960 inches and 0.9965 inches **Second End Distance From End To Groove:** Between 0.740 inches and 0.800 inches **Second End Diameter:** Between 1.0440 inches and 1.5440 inches Second End Spline Length: Between 0.740 inches and 0.800 inches **Second End Spline Minor Diameter:** 0.9080 inches **Second End Spline Major Diameter:** Between 1.0440 inches and 1.0540 inches Second End Internal Thread Length: 0.690 inches

Step Quantity:

\_ ---

Second End Spline Quantity:

19

**Largest Step Diameter:** 

Between 1.2495 inches and 1.2500 inches

**Special Features:** 

Ninternal thread on second end is 0.3125-24unf-2b; spline b on first end, second step has major diameter 1.232-1.242 in., length 1.000-1.060 in.; omit one tooth each spline to be in line with each other within 1 degree

Material:

Steel comp 8655

**Material Specification:** 

Qq-s-624 federal specification all material responses

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

## NSN 3040-00-735-9091

Shouldered Shaft - Page 2 of 2



Demilitarization:

No

Fiig:

A23200