

View Online at <https://aerobasegroup.com/nsn/3040-00-757-3347>

General Description:

Cres, ams5643, 0.274 in. Min, 0.277 in. Maximum dia, 0.032 in. Min, 0.038 in. Maximum lg of first step, 0.288 in. Min, 0.292 in. Maximum diameter of groove, 0.029 in. Min, 0.032 in. Maximum w, 0.300 in. Min, 0.310 in. Maximum dia, 0.030 in. W second step, 0.300 in. Min, 0.310 in. Maximum diameter of groove, 0.030 in. W, 0.3144 in. Min, 0.3147 in. Maximum diameter of third step, 0.300 in. Min, 0.310 in. Maximum diameter of groove, 0.030 in. W, on left end, 0.345 in. Min, 0.348 in. Maximum od, external spline drive, 48/96 pitch, 16 tooth, 30 degrees pressure angle, 0.274 in. Min, 0.281 in. Maximum minor dia, 0.345 in. Min, 0.348 in. Maximum major dia, internal spline drive, 48/96 pitch, 8 tooth, 30 degrees pressure angle, 0.1499 in. Min, 0.1514 in. Maximum minor dia, 0.198 in. Min, 0.203 in. Maximum major dia

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No