

NSN 3040-00-759-1797 Flexible Shaft Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-00-759-1797 **Thread Class:** 2b first end **Thread Direction:** Right-hand both ends Thread Length: 0.375 inches both ends **Overall Length:** 18.750 inches **Wrenching Facility Outside Diameter:** 1.000 inches both ends **Thread Depth:** 0.250 inches both ends Tip Length: 1.000 inches second end **Shank Outside Diameter:** 0.531 inches both ends **Shoulder Outside Diameter:** 1.000 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Unf both ends **Core Surface Treatment:** Cadmium plated **Core Diameter:** 0.188 inches **Thread Location:** Internal first end **End Type:** Round keyed first end

End Connection Type:

Threaded internal first end

Setscrew:

Not included both ends

Casing Material:

Steel

Wrenching Facility Type:

Knurled surface both ends

Cross Section Size And Location:

0.406 inches diameter second end

Machined Feature Size:

0.047 in.W x 0.500 in.Lg key; 0.047 in.W x 0.938 in.Lg x 0.125 in.Dp slot

NSN 3040-00-759-1797

Flexible Shaft Assembly - Page 2 of 2



Casing Surface Treatment:
Cadmium plated
Casing Length Between Ferrules:
13.750 inches
Casing Outside Diameter:
0.445 inches
Casing Protective Device Type:
Flexible steel hose protector
Swivel End:
Not provided both ends
Enddiameter:
0.875 inches second end
Lubrication Fitting:
Not provided both ends
Corelength:
18.750 inches
Core Rotation Direction:
Clockwise
Core Removability:
Removable
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
T246-e