

View Online at <https://aerobasegroup.com/nsn/3040-00-759-1797>

**Thread Class:**

2b first end

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.375 inches both ends

**Overall Length:**

18.750 inches

**Wrenching Facility Outside Diameter:**

1.000 inches both ends

**Thread Depth:**

0.250 inches both ends

**Tip Length:**

1.000 inches second end

**Shank Outside Diameter:**

0.531 inches both ends

**Shoulder Outside Diameter:**

1.000 inches both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Unf both ends

**Core Surface Treatment:**

Cadmium plated

**Core Diameter:**

0.188 inches

**Thread Location:**

Internal first end

**End Type:**

Round keyed first end

**End Connection Type:**

Threaded internal first end

**Setscrew:**

Not included both ends

**Casing Material:**

Steel

**Wrenching Facility Type:**

Knurled surface both ends

**Cross Section Size And Location:**

0.406 inches diameter second end

**Machined Feature Size:**

0.047 in.W x 0.500 in.Lg key; 0.047 in.W x 0.938 in.Lg x 0.125 in.Dp slot

**Casing Surface Treatment:**

Cadmium plated

**Casing Length Between Ferrules:**

13.750 inches

**Casing Outside Diameter:**

0.445 inches

**Casing Protective Device Type:**

Flexible steel hose protector

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.875 inches second end

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

18.750 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Removable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T246-e