

View Online at <https://aerobasegroup.com/nsn/3040-00-767-7915>

**Thread Class:**

2a both ends

**Thread Direction:**

Right-hand both ends

**Thread Length:**

0.313 inches both ends

**Overall Length:**

12.438 inches

**Wrenching Facility Outside Diameter:**

0.562 inches both ends

**Tip Length:**

0.875 inches second end

**Shank Outside Diameter:**

0.250 inches both ends

**Shoulder Outside Diameter:**

0.406 inches both ends

**Tongue Thickness:**

0.219 inches both ends

**Core Material:**

Steel

**Screw Thread Series Designator:**

Unf both ends

**Core Diameter:**

0.150 inches

**Thread Location:**

External both ends

**End Type:**

Round, flatted two sides, external first end

**End Connection Type:**

Shouldered ferrule both ends

**Tongue Length:**

0.375 inches both ends

**Setscrew:**

Not included first end

**Casing Material:**

Phosphor bronze

**Wrenching Facility Type:**

Hexagon both ends

**Cross Section Size And Location:**

0.500 inches diameter second end

**Machined Feature Size:**

0.187 in. Diameter by 0.375 in. Deep bore

**Torsional Deflection Rating:**

6 degrees ft-lb in. Torsional in winding direction and 7 degrees ft/lb in. Torsional deflection in unwinding direction

**Casing Length Between Ferrules:**

10.000 inches

**Casing Outside Diameter:**

0.235 inches

**Swivel End:**

Not provided both ends

**Enddiameter:**

0.562 inches both ends

**Lubrication Fitting:**

Not provided both ends

**Corelength:**

12.438 inches

**Core Rotation Direction:**

Clockwise

**Core Removability:**

Nonremovable

**Minimum Operating Radius:**

3.500 inches

**Special Features:**

Core matl outer layer monel

**Fsc Application Data:**

Radar set, nonairborne, except fire control and guided missiles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T246-e