

View Online at <https://aerobasegroup.com/nsn/3040-00-857-9796>

**Outside Diameter:**

1.500 inches

**Thickness:**

0.500 inches

**Bore Diameter:**

Between 0.7520 inches and 0.7550 inches

**Securing Hole Quantity:**

2

**Angle Between Centerlines Of Securing Holes In Deg:**

180.0

**Securing Hole Type And Location:**

Unthreaded all holes

**Hole Diameter And Location:**

0.2500 inches all holes and 0.2560 inches all holes

**Material:**

Steel, federal standard 66, aisi b1111 or steel, federal standard 66, aisi b1112, 1212/sae 1112 or steel, federal standard 66, aisi b1113, 1213/sae 1113 or steel, qq-t-830 comp mt 1015 through mtx 1020

**Material:**

Steel comp 1211 or steel comp b1112 or steel comp 1212 or steel comp 1213 or steel, qq-t-830 comp mt 1015 through mtx 1020

**Material Specification:**

Fed standard 66 federal standard 1st material response or aisi b1111 assn standard single material response and federal standard 66 federal standard 2nd material response or aisi b1112, 1212 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Style Designator:**

Plain round

**Surface Treatment:**

Cadmium, qq-p-416, type 2, class 1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A231a0