## NSN 3040-00-868-5548

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-868-5548 **Body Material:** Any acceptable **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** Not rated **Overall Height: 5.375** inches **Overall Width: 6.750** inches **Bore Diameter:** 4.000 inches **Longest Horizontal Distance Between Mounting Centers:** 6.625 inches **Longest Vertical Distance Between Mounting Centers:** 5.750 inches **Compressed Length:** 16.500 inches **Extended Length:** 16.500 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 2350.0 pounds per square inch **Integral Valve Operation Method:** Mechanical **Design Characteristics:** Double acting single cylinder First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.375 inches First Piston Rod End Thready Qty Per Inch (tpi): 24 **First Piston Rod End Thread Class:** 2b **First Piston Rod End Thread Direction:** Right-hand **Piston Rod End Similarity:** 

Identical

**Mounting Type And Location:** 

Flange center section

NSN 3040-00-868-5548 Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Diameter:
0.397 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Nptf
Port Thread Diameter:
0.250 inches
Port Pipe Thread Size:
0.250 inches
Special Features:
Piston rod end thd, 0.750 in. Deep; flange welded to side of cylinder w/four thd holes, three holes 0.250-28 unf, one hole 0.127-27 nftf
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A34200