## NSN 3040-00-872-5103

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-872-5103 **Body Material:** Zinc alloy **Mounting Provision:** Threaded mounting studs **Mounting Facility Length:** Between 0.625 inches and 1.000 inches **Bore Diameter:** 2.750 inches **Overall Diameter:** 4.500 inches **Longest Horizontal Distance Between Mounting Centers:** 1.750 inches **Shortest Horizontal Distance Between Mounting Centers:** 1.375 inches **Longest Vertical Distance Between Mounting Centers:** 2.750 inches **Mounting Facility Thread Class:** 2a **Mounting Facility Thread Direction:** Right-hand First End Hole Diameter: 0.218 inches **Compressed Length:** 6.656 inches **Extended Length:** 9.656 inches **Mounting Provision Arrangement Style:** Three stud triangular **Pressure Rating:** 20.0 pounds per square inch **Mounting Facility Thread Series Designator: Mounting Facility Thread Diameter:** 0.156 inches Mounting Facility Thready Qty Per Inch (tpi): **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Fork type (clevis)

First End Largest Inside Diameter:

0.218 inches

## NSN 3040-00-872-5103

Linear Actuating Cylinder Assembly - Page 2 of 2



First End Fork Width:
0.625 inches
First End Fork Depth:
1.000 inches
First End Fork Span Width:
0.250 inches
Mounting Type And Location:
Stud center section
Mounting Facility Thread Length
0.750 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A34200