NSN 3040-00-902-5319

Linear Actuating Cylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-902-5319

	ate	

Aluminum alloy, qq-a-225/4, alloy 2014, t6

Mounting Provision:

Unthreaded mounting holes

Overall Length:

Between 5.790 inches and 5.810 inches

Overall Height:

Between 3.100 inches and 3.160 inches

Overall Width:

Between 3.810 inches and 3.870 inches

Bore Diameter:

Between 1.616 inches and 1.618 inches

Body Outside Diameter:

Between 2.290 inches and 2.310 inches

Longest Horizontal Distance Between Mounting Centers:

Between 3.240 inches and 3.260 inches

Longest Vertical Distance Between Mounting Centers:

Between 2.990 inches and 3.010 inches

Seat Angle In Deg:

60.5 all ports

Mounting Provision Arrangement Style:

Four hole rectangular

Mounting Type And Location:

Lug center section

Mounting Facility Diameter:

0.400 inches

Port Location And Quantity:

2 center section

Port Style:

Gasket seal all ports

Port Thread Series Designator:

Unif all ports

Port Thread Diameter:

0.438 inches all ports

Port Thready Qty Per Inch (tpi):

20 all ports

Port Thread Class:

3b all ports

Fsc Application Data:

Aft landing gear

Shelf Life:

N/a

NSN 3040-00-902-5319

Linear Actuating Cylinder - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A34200