## NSN 3040-00-905-6534

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-905-6534

First End Style:

Unthreaded cross drilled

**End Similarity:** 

Not identical

Second End Style:

Cross drilled hole and splined (straight)

**Overall Length:** 

4.000 inches

First End Diameter:

Between 0.2498 inches and 0.2500 inches

First End Hole Diameter:

Between 0.0940 inches and 0.0970 inches

First End Distance From Hole Center To End:

1.396 inches

First End Hole Depth:

Any acceptable

**Second End Diameter:** 

Between 0.2498 inches and 0.2500 inches

Second End Spline Length:

0.280 inches

**Second End Spline Minor Diameter:** 

0.2063 inches

**Second End Spline Major Diameter:** 

0.2500 inches

**Second End Hole Diameter:** 

Between 0.0940 inches and 0.0970 inches

**Second End Distance From Hole Center To End:** 

0.250 inches

Second End Hole Depth:

Any acceptable

Step Quantity:

2

**Second End Spline Quantity:** 

11

**Largest Step Diameter:** 

Between 0.295 inches and 0.305 inches

Surface Finish:

62.0 microinches

**Special Features:** 

Involute spline 1.094 in. From 2nd end

Material:

Steel comp 416

## NSN 3040-00-905-6534

Shouldered Shaft - Page 2 of 2



Material Specification:
-------------------------

Qq-s-763, cond a federal specification single material response

**Fsc Application Data:** 

Sonar set

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200