NSN 3040-00-913-0549

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-913-0549

First End Style:

Woodruff keyway

End Similarity:

Not identical

Second End Style:

Circular grooved and flat keyway

Second End Groove Width:

Between 0.0300 inches and 0.0330 inches

Second End Groove Diameter:

Between 0.4170 inches and 0.4270 inches

Overall Length:

5.080 inches

First End Keyway Width:

Between 0.0928 inches and 0.0943 inches

First End External Keyway Length:

0.500 inches

First End Distance From Keyway Center To End:

0.320 inches

First End Diameter:

Between 0.4985 inches and 0.4990 inches

Second End Distance From End To Groove:

Between 0.070 inches and 0.073 inches

Second End Keyway Width:

Between 0.1270 inches and 0.1300 inches

Second End External Keyway Length:

Between 0.945 inches and 0.958 inches

Second End Keyway Depth:

Between 0.072 inches and 0.081 inches

Second End Diameter:

Between 0.4980 inches and 0.4990 inches

Second End Hole Diameter:

Between 0.1270 inches and 0.1300 inches

Second End Distance From Hole Center To End:

Between 0.465 inches and 0.475 inches

Step Quantity:

_

Largest Step Diameter:

0.562 inches

Special Features:

Angle between keyways 180 deg

Material:

Steel comp 440c

NSN 3040-00-913-0549

Shouldered Shaft - Page 2 of 2



M	late	rial	Sp	ecif	icat	ion:
			~	••••		. •

Qq-s-763 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200