NSN 3040-00-936-5204



| Flexible Shaft Assembly - Page 1 of 2 | Group |
|---|-------|
| View Online at https://aerobasegroup.com/nsn/3040-00-936-5204 | |
| Thread Class: | |
| 2b both ends | |
| Thread Direction: | |
| Right-hand both ends | |
| Overall Length: | |
| 5.665 inches | |
| Thread Depth: | |
| 0.438 inches both ends | |
| Tip Length: | |
| 1.125 inches first end | |
| Shoulder Outside Diameter: | |
| 0.740 inches both ends | |
| Core Material: | |
| Steel | |
| Core Surface Treatment: | |
| Copper plated | |
| Core Diameter: | |
| 0.150 inches | |
| Thread Location: | |
| Internal both ends | |
| End Type: | |
| Square female second end | |
| Width Across Flats: | |
| 1.000 inches both ends | |
| End Connection Type: | |
| Union ferrule both ends | |
| Casing Material: | |
| Steel | |
| Wrenching Facility Type: | |
| Hexagon both ends | |
| Cross Section Size And Location: | |
| 0.325 inches across flats second end | |

Casing Surface Treatment:

Cadmium plated

Casing Length Between Ferrules:

2.280 inches

Casing Outside Diameter:

0.438 inches

Casing Protective Device Type:

Flexible steel hose protector

Swivel End:

Not provided both ends

NSN 3040-00-936-5204Flexible Shaft Assembly - Page 2 of 2



| Corelength: |
|--------------------------|
| 4.000 inches |
| Core Rotation Direction: |
| Clockwise |
| Core Removability: |
| Removable |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: T246-e