

View Online at <https://aerobasegroup.com/nsn/3040-00-950-9365>

**Outside Diameter:**

0.437 inches

**Thickness:**

0.218 inches

**Small End Diameter:**

0.250 inches

**Bore Diameter:**

0.1870 inches

**Largest Diameter Length:**

0.156 inches

**Securing Hole Quantity:**

2

**Angle Between Centerlines Of Securing Holes In Deg:**

90.0

**Screw Thread Series Designator And Location:**

2nd hole unc

**Securing Hole Type And Location:**

Threaded 2nd hole

**Thread Size And Location:**

0.112 inches 2nd hole

**Hole Diameter And Location:**

0.0460 inches 1st hole

**Material:**

Steel, qq-s-763

**Material:**

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Round stepped

**Surface Treatment:**

Passivated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**