NSN 3040-00-979-0133

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-00-979-0133 **Thread Class:** 2b both ends **Thread Direction:** Right-hand both ends **Spline Major Diameter:** 0.271 inches both ends **Overall Length:** 24.000 inches **Spline Quantity:** 12 both ends **Spline Minor Diameter:** 0.229 inches both ends **Wrenching Facility Outside Diameter:** 0.764 inches both ends **Thread Depth:** 0.375 inches both ends **Pitch Diameter:** 0.250 inches both ends **Core Material:** Steel **Screw Thread Series Designator:** Un both ends **Core Surface Treatment:** Zinc coated **Core Diameter:** 0.140 inches **Thread Location:** Internal both ends **End Type:** Round, internal splined both ends **End Connection Type:** Union ferrule both ends Spline Pressure Angle In Deg: 30.0 both ends Spline Length: 0.250 inches both ends Spline Type: Involute both ends **Casing Material:** Steel

Wrenching Facility Type: Knurled surface both ends

NSN 3040-00-979-0133Flexible Shaft Assembly - Page 2 of 2



Casing Length Between Ferrules:
23.000 inches
Casing Outside Diameter:
0.250 inches
Casing Protective Device Type:
Plastic cover
Swivel End:
Not provided both ends
Enddiameter:
0.764 inches both ends
Lubrication Fitting:
Not provided both ends
Corelength:
23.125 inches
Core Rotation Direction:
Clockwise
Core Removability:
Nonremovable
Shelf Life:
N/a
Unit Of Measure:
. -
Demilitarization:
No
Fiig:
Г246-е